國立臺灣海洋大學 101 學年度研究所碩士班暨碩士在職專班入學考試試題

考試科目:控制系統

系所名稱:通訊與導航工程學系碩士班控制組


* 可使用計算器

1.答案以橫式由左至右書寫。2.請依題號順序作答。

(20%) Consider a single-loop feedback control system has the loop transfer function 1.

$$L(s) = G(s)H(s) = \frac{K}{s(s+2)(s+10)}.$$

- (a) Draw the Nyquist plot of L(s)/K for $\omega = \infty$ to $\omega = 0$.
- (b) Find the range of K such that the system is stable.
- (20%) A unit feedback system is given as follow: 2.



Find the steady-state error when the input is:

- (a) unit-step function
- (b) unit-ramp function
- (e) unit-parabolic function
- (20%) Consider a servo motor position control system as follow:

$$\begin{array}{c}
R \\
+ \\
 \end{array}$$

$$\begin{array}{c}
C \\
\hline
s(0.25s+1)
\end{array}$$

- (a) Find the range of K such that the system is stable.
- (b) For a unit-step input, find the value of K such that the system has critical-damped response.
- (c) Continue from part (b). Find the critical-damped response and steady-state value of the system.
- 4. (20%) Consider the system with

(20%) Consider the system with
$$G(s) = \frac{K}{(T_1 s + 1)(T_2 s + 1)}; \text{ where } T_1 = 1, T_2 = 0.5.$$

- (a) Construct root loci for $K \ge 0$.
- (b) Locate the roots for $K=0, 0.125, \text{ and } \infty$.
- (c) If we add a zero at -5, draw the new root locus and describe the effect on system stability.
- (d) If we add a pole instead of a zero at -5, draw the new root locus and describe the effect.
- (20%) Consider a system with following dynamic equations:

$$\dot{X}(t) = AX(t) + Bu(t), \quad y(t) = CX(t) + Du(t)$$

where
$$X(t) = \begin{bmatrix} x_1(t) \\ x_2(t) \end{bmatrix}$$
, $A = \begin{bmatrix} 0 & 1 \\ -2 & -3 \end{bmatrix}$, $B = \begin{bmatrix} 0 \\ 1 \end{bmatrix}$, $C = \begin{bmatrix} 1 & 0 \end{bmatrix}$, $D = \begin{bmatrix} 0 \end{bmatrix}$.

- (a) Assume that the initial conditions of x_1 and x_2 are $x_1(0) = 1$ and $x_2(0) = 1$, respectively. Find the output y(t) for $t \ge 0$, where u(t) is the input of the system and is a unit-step function.
- (b) Is this system stable with step function input? Explain why.